


LEGEND

- ① SERVICE SADDLE, FORD, S91 ON C900 PVC MAIN, FORD FC 202 WITH 1-1/4" OUTLET WITH INSULATING BUSHING ON D.I. PIPE.
- (2) 1" BALL CORPORATION STOP, FORD FB1101 NPT \times PACK JOINT. (3) 1" DIA. PIPE HDPE SDR 11 SERVICE PIPE, IPS OD. UNIONS OR COUPLINGS NOT PERMITTED. STAINLESS STEEL INSERT STIFFENERS EA. END. 4" BEDDING MATERIAL AROUND PIPE.
- 3/4" CRUSHED DRAIN ROCK (AS DIRECTED BY DISTRICT ENGINEER).
- 1" BRANCH BALL VALVE ASSEMBLY, FORD UVB63-42W-65.
- METER WITH AMR TRANSMITTER (FURNISHED BY DISTRICT).
- DUAL CHECK VALVE, METER COUPLING x NPT, FORD HHS91-323 STRAIGHT CASCADING.
- METER BOX, CARSON NO. 1419 WITH NO. 1419-3 FLUSH COVER LOCKING LID AND APPROVED BASE, FOR USE IN NON-VEHICULAR TRAFFIC/PARKING SITUATIONS ONLY. CONTACT DISTRICT ENGINEER IF INSTALLATION IS TO BE IN VEHICULAR TRAFFIC AND PARKING AREAS.
- STRAIGHT BALL VALVE, FORD B11-333 WITH FORD HB-34S HANDLE.
- CUSTOMER VALVE BOX, CHRISTY NO. F8 WITH NO. F8D ACCESS LID.
- (1) 1" DIA. X 18" LONG SCH, 80 PVC PIPE, THREADED.

STANDARD 1" DUAL SERVICE CONNECTION $(5/8" \times 3/4" \text{ METERS})$

N.T.S.

	Transference and t
GROVELAND COMMUNITY SERVICES DISTRICT	REV: 7/2019
STANDARD WATER SYSTEM DETAIL	NO. S2
	- Anna Comment of the



LEGEND

- ① SERVICE SADDLE, FORD, S91 ON C900 PVC MAIN, FORD FC 202 WITH 1-1/4" OUTLET WITH INSULATING BUSHING ON D.I. PIPE.
- 3 1" BALL CORPORATION STOP, FORD FB1101 NPT x PACK JOINT. 3 1" DIA. PIPE HDPE SDR 11 SERVICE PIPE, IPS OD. UNIONS OR COUPLINGS NOT PERMITTED. STAINLESS STEEL INSERT STIFFENERS EA. END. 4" BEDDING MATERIAL AROUND PIPE.
- 3/4" CRUSHED DRAIN ROCK (AS DIRECTED BY DISTRICT ENGINEER).
- BALL ANGLE LOCKING METER STOP, FORD BA63-332W.
- METER WITH AMR TRANSMITTER (FURNISHED BY DISTRICT).
- DUAL CHECK VALVE, METER COUPLING x NPT, FORD HHS91-323 STRAIGHT CASCADING.
- METER BOX, CARSON NO. 1419 WITH NO. 1419-3 FLUSH COVER LOCKING LID AND APPROVED BASE. FOR USE IN NON-VEHICULAR TRAFFIC/PARKING SITUATIONS ONLY. CONTACT DISTRICT ENGINEER IF INSTALLATION IS TO BE IN VEHICULAR TRAFFIC AND PARKING AREAS.
- STRAIGHT BALL VALVE, FORD B11-333 WITH FORD HB-34S HANDLE.
- O CUSTOMER VALVE BOX, CHRISTY NO. F8 WITH NO. F8D ACCESS LID.
- (1) 1" DIA. X 18" LONG SCH. 80 PVC PIPE, THREADED.

STANDARD 1" SINGLE SERVICE CONNECTION $(5/8" \times 3/4" METER)$

\$ % B	(18 <u> </u>
GROVELAND COMMUNITY SERVICES DISTRICT	REV: 7/2019
STANDARD WATER SYSTEM DETAIL	NO. S1